



INDUSTRIAL Diesel Generator MODEL:EDG-60

Specification & Application Data

Rating Range – 60Hz Operation

Standby	kW	56-65
	kVA	70-81
Prime	kW	54-59
	kVA	68-74
Sound Attenuation:		
	At 7m / 23 ft	71dB

KEY FEATURES

ELECON industrial generators are efficient, Reliable and versatile source of power for Standby or Prime Power Applications. All generator sets and components are factory built, and productions tested. The Genset features a heavy-duty John Deere 4- cycle Diesel engine certified by the Environmental Protection Agency (EPA) to conform to Tier 3 non-road emission Regulations, an AC high capability alternator regulated by a precise Automatic Voltage Regulator. Heavy- duty Constructed chassis supports the complete set. The generator is protected by a best-in-class sound Attenuated enclosure designed for prime or standby applications.

- Engine – generating set tested to ISO 8528-5.
- The Genset engine is certified by the Environmental Protection Agency (EPA) Tier 3 non-road emission regulations
- The brushless, single bearing, 4 poles, 12-wire generator end, with automatic voltage regulator has broad range reconnect ability.
- The Genset is CSA certified.
- Integral vibration isolation rubbers eliminate the need of vibration spring isolators.
- Global product support.
- Operations and maintenance manuals.
- One Year Warranty Standard, Extended warranties are also available.
- Heavy duty construction that is designed for use in prime or standby applications.
- Assembled in Canada.

GENSET RATINGS

GENSET Model	ENGINE Model	ALTERNATOR Model	VOLTAGE N-L L-L	Ph	Hz	150°C RISE			125°C RISE		
						STANDBY RATING			PRIME RATING		
						kW	kVA	Amps	kW	kVA	Amps
EDG-60		UCI 224 F	120/208	3	60	64	80	223	58	73	202
			277/480	3	60	65	81	97	59	73	88
		UCI 224 F	347/600	3	60	65	81	78	59	73	71

Ratings: Standby ratings are continuous for the duration of any power outage. No overload capacity is specified at this rating. Prime ratings are continuous per BS5514, DIN 6271, IDO-3046, and IEC34-1 with 10% overload capacity one hour in twelve hours. Larger alternators may be used to meet special application requirements. Elecon reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever.

GENERAL GUIDELINES FOR DERATION: ALTITUDE: Derate 1.5% per 1000ft. (305 m) elevation above 3300ft (1003 m) TEMPERATURE: Derate 0.5% per 10°F (5.5°C) temperature above 77°F (25°C)

Specification & Application Data

Engine Specification

GENERAL DATA			
Manufacturer	JOHN DEERE		
Engine model	4045HF280		
EPA Certification for:	Stage	Tier 3	
Rated	RPM	1800	
Nominal Power (PRIME)	kW – HP	67	90
Nominal Power (STANDBY)	kW – HP	74	99
Engine type	Diesel 4 stroke		
Injection type	DIRECT		
Aspiration type	INTERCOOLED		
Cylinder arrangement	4 – L		
Bore and stroke	(mm) – In	(106 x 127)	4.19 x 5.00
Displacement	L – in3	4.5	275
Cooling system	Liquid		
Governor type	Mechanical		
Air cleaner type	Medium duty w/double cartridge		
Compression ratio	19.0 : 1		

Application data

EXHAUST SYSTEM		PRIME	STANDBY
Exhaust manifold type		Dry	Dry
Exhaust outlet diameter	mm - In	90 – 3.546	
Max. Exhaust temp. at full load	°C	515	545
	°F	959	1013
Exhaust Gas Flow	kg/h – Lb/h	340.2 – 750.01	362.88 – 800.01
	(m3/min) – ft3/min	(13.5) - 477	(14.4) – 508
Maximum allowed back pressure	(mm/H2O) – inH2O	762 – 30	

COOLING SYSTEM		
Engine cooling air flow	m3/s – ft3/s	3.8 – 133.4
Generator cooling air flow	m3/min – ft3/min	16.9 – 595.4
Total cooling air flow (engine + generator + combustion)		
Open Skid version	m3/min – ft3/min	498.0 – 17,586.7
Sound Attenuated version	m3/min – ft3/min	648.0 – 22,883.9
Total cooling capacity	l – gal	27.1 – 7.2
Antifreeze recommended	l – gal	13.6 – 3.6

Specification & Application Data

LUBRICATION SYSTEM		
Oil Filter: quantity. Type		1 x Cartridge
Oil pan capacity	l – gal	15 – 3.96
Oil pan capacity with filter	l – gal	12 – 3.17
Oil cooler		Water Cooled
Recommended oil		15W-40 or API CI-4 PLUS o CI-4
Specific oil consumption full load	% fuel	<0.1% <0.1%
Oil Press	(psi) – kPa	46 - 320

VENTILATION REQUIREMENTS		
Air requirement for combustion at 100% load/rated speed	m3/h – ft3/h	324 – 11460
Cooling airflow	m3/h – ft3/h	--
Heat rejected to ambient:		
From engine	kW – btu/min	35 – 1979
From alternator	kW – btu/min	1.4 – 79.67

ELECTRICAL SYSTEMS		12V
Ground (negative/positive)		Negative
Volts (DC)	V	12
Ampere rating	Amp	55
Starter motor rated voltage (DC)	V	12
Starter motor rated	kW / HP	1.46 / 1.99
Battery recommendations		
Min. Cold Cranking Amps	Amp	640

FUEL SYSTEMS		
Recommended fuel		#2 Diesel
Fuel supply line. min. ID	mm – in	11 0.44
Fuel return line. min. ID	mm – in	6 0.24
Fuel pump Type		Engine Driven
Secondary filter		5µm @ 98 % Eff.
Secondary Water Separator		Included

		PRIME rating		STANDBY rating	
		l/h	gal/h	l/h	gal/h
100% Load	l/h – gal/h	17.8	4.7	19.4	5.1
75% Load	l/h – gal/h	13.6	3.6	14.9	3.9
50% Load	l/h – gal/h	9.6	2.5	10.6	2.8
25% Load	l/h – gal/h	5.4	1.4	5.9	1.5

Specification & Application Data

Alternator Specifications

GENERAL DATA	
Manufacturer	Stamford
Model (480V)	UCI 224 f
Alternator Type	4 poles, rotating field
Exciter Type	Brushless, self-excited
	PMG (optional)
Leads: quantity, type	12, reconnectable
Stator Pitch	2/3
Insulation system	
Material	Class H
Temperature rise	150 °C Standby 125 °C Prime
Bearing: quantity, type	Single bearing sealed
Coupling	Flexible disc
Automatic Voltage regulator	
STD regulator	SX460
PMG regulator or EBS	Opt MX341, Opt MX321
Voltage regulation, no load to full load	
STD regulator	+/-1.5%
PMG regulator load acceptance	+/-1%, +/-0.5%

SOUND ATTENUATED MODEL

STANDARD SIZE (Size W/Extended Capacity, Tank)	(Length x Width x Height)			
	mm	2,750 x 1,100 x 1940		
	in	108.3 x 43.3 x 76.4		
Dry weight (with std. accessories)	kg Lb	2,116	4,665	
Fuel Tank Capacity	L Gal	540	142.6	
Run Time (Hr)	100 %	75%	50%	25%
Prime Power	30.5	39.5	55.9	99.2
Standby Power	27.9	36.1	51.1	92.0
Noise level	7 m	71 dba		

OPEN SKID MODEL

Overall size (L x W x H)	(Length x Width x Height)		
	mm	2,032 x 813 x 1,350	
	in	80 x 32 x 53	
Dry weight (with std. accessories)	kg Lb	1,010	2,220
Fuel Tank Capacity	Optional		

